



POS sockets in 7,62mm/.300" DIP spacing are either supplied with or without bars in the centre depending on plastic wafer availability. If you need sockets without centre bars, then please always order with POO instead of POS.

Pin	Dimension		Available Pinouts of Series		
	"A"	"B"	POS	POO	PCL
10	12,60	5,08 .200"	-	-	-210-
6	7,60	7,62 .300"	-306-	-	-
8	10,10		-308-	-	-
10	12,60		-310-	-	-
14	17,70		-314-	-314-	-314-
16	20,30		-316-	-316-	-316-
18	22,80	7,62 .300"	-318-	-318-	-318-
20	25,30		-320-	-320-	-320-
22	27,80		on request	on request	-
24	30,40		-324-	-324-	-
28	35,50		-328-	-328-	-
16	20,32	10,16 .400"	on request	on request	on request
22	27,80				
24	30,60				
24	30,50	15,24 .600"	-624-	-624-	on request
28	35,50		-628-	-628-	-628-
32	40,60		-632-	-632-	-632-
36	45,70		-636-	on request	-
40	50,80		-640-	-640-	-640-
48	60,96		-648-	on request	on request
64	81,26	22,86 .900"	on request	-	-

<p>001 Standard terminal</p>	<p>047 Low profile terminal</p>
<p>008 long tail terminal</p>	<p>003 3-level w/w</p>
<p>009 extra long tail terminal</p>	<p>010 Carrier terminal</p>

Specifications
PBT and high temp plastic depending on type.
See page 49 of this catalogue and contact factory for more details.

Insulator body

POS series = open insulator - see drawings above
POO series = open insulator w/o centre bars
PCL series = closed insulator body

Terminals
The POS, POO and PCL series are available with many different terminal styles. The most common terminal styles are shown on the right hand side of this page. Many other additional terminals can be found at the end of this catalogue. Custom design terminals are available on request.

How to order

XXX - x xx - Sxxx - xx

Series	DIP spacing (inch)	Nbr of contacts	Terminal style	Plating
POS	see above table, dimension "B"	see above table	see drawings above	- 95 = tin/gold
POO	Example: 3 for .300"	Example: 06 for 6 Pin	or refer to pages 46 to 48 of this catalogue for other types.	- 55 = gold/gold
PCL	insert the corresponding data of the POS, POO or PCL column			- 99 = tin/tin (tin leadfree)